
VERTICAL 20mm COIN CELL

This space saving vertical design features a rugged, lightweight body that mounts squarely and securely on PC boards for easy installation and replacement of batteries. Reliable spring tension assures low contact resistance.

- Accepts all major manufacturers' 20mm diameter batteries
- Molded notch prevents improper insertion of 2032 size cells
- Space saving design for high density packaging
- Retains cells securely, withstands shock and vibration
- Polarity clearly marked Mounts securely for wave soldering
- Temperature range -60°F to +293°F (-50°C to +145°C)

COMPACT



MATERIAL:

Contacts: .012 (.30) thick Spring Steel, Tin Nickel Plate

Base: PBT, UL Rated 94V-0

CAT. NO. 1067



A "unique" space saving design. The battery is installed vertically from the top. The contacts of this holder are polarized to assure proper continuity and circuit protection. Polarized holder Mounts securely for wave soldering Reliable spring tension assures low contact resistance Retains 20mm batteries securely to withstand shock and vibration Temperature range -60°F to +293°F (-50°C to +145°C) 1.040 [26.4] POSITIVE -.300 [7.6] NEGATIVE -.920 [23.4] --.238 [6.1] .795 [20.2] POS [25.4] REF. .918 [23.3] 150 SLIMLINE 1

.193

Contacts: .016 (.41) thick Spring Steel, Tin Nickel Plate


.600 [15.2]

.070 [1.78]

.145 [3.7]

Base: PBT, UL Rated 94V-0

CAT. NO. 1065



.050 [1.27] (2) PLS

.315 [8.0]



Semic Trade, s.r.o. Volutová 2521/18 158 00 Praha 5 Czech Republic

www.semic.cz www.semic-shop.cz semic@semic.cz

tel.: +420 251 625 331, 332, 377