



PCB Layout Diagram
Top View

NOTE:

1. MATERIAL:

a. HOUSING: THERMOPLASTIC GLASS FIBRE UL94V-0

MATERIAL:

- C0170-02ATB000R: PBT, BLACK
- C0170-02ATB000L: PA66, BLACK
- C0170-02ATB000C: PPS, BLACK
- C0170-02ATN000C: PPS, BROWN
- C0170-02ATW000N: LCP, WHITE
- C0170-02ATB000N: LCP, BLACK

b. CONTACT: Mn Steel

(SURFACE PLATING: Ni100u")

SEE ORDERING INFORMATION

2. ELECTRIC:

- a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
- d. OPERATING TEMPERATURE: -25° C ~ +85° C

B-Držák-2032/BH3

RoHS
Compliant

SEMIC
TRADE

SEMIC TRADE, s.r.o.
Volutova 2521/18
158 00 Praha 5
Czech Republic
www.semic.cz
semic@semic.cz
tel.: +420 251 625 331, 332, 377
fax: +420 251 626 252, 393

APPD. 核准	SCALE 比例	TOLERANCE 容許公差
DWG. 製圖	UNIT 單位	SIZE. 紙張尺寸
DATE 制表日	PAGE 張數	REV. 版次
Helen	M M	A 4
2016/6/28	1 OF 1	B

PART NAME 品名	BATTERY HOLDERS BH3 TYPE ROHS
PART NO. 料號	C0170-02ATX000X