


FRX90V Series

RoHS Compliant & Lead Free)



Application:

Telecom & wide variety of electronic equipment

Product Features:

Low hold current, Solid state, Radial leaded product ideal for up to 90V

Operation Current: 0.10A~3.75A

Maximum Voltage: Up to 90V

Temperature Range: -40°C to 85°C

Agency Recognition: UL (E211981)

C-UL (E211981)

*TÜV (R50004084)


Electrical Characteristics (23°C)

Part Number	Hold Current I _H , A	Trip Current I _T , A	Max.Time to Trip at 5xI _H , s	Max. Current I _{MAX} , A	Rated Voltage V _{MAX} , V _{DC}	Typical Power Pd, W	Resistance Tolerance	
							R _{MIN} Ohms	R _{1MAX} Ohms
FRX010-90F	0.10	0.20	4.0	40	72/90	0.38	2.50	7.50
FRX015-90F	0.15	0.35	10.0	40	72/90	0.70	2.40	7.00
FRX017-90F	0.17	0.34	3.0	40	72/90	0.48	2.00	8.00
FRX020-90F	0.20	0.40	2.2	40	72/90	0.41	1.83	4.40
FRX025-90F	0.25	0.50	2.5	40	72/90	0.45	1.25	3.00
FRX030-90F	0.30	0.60	3.0	40	72/90	0.49	0.88	2.10
FRX035-90F	0.35	0.75	10.0	40	72/90	1.30	0.70	2.50
FRX040-90F	0.40	0.80	3.8	40	72/90	0.56	0.55	1.29
FRX050-90F	0.50	1.00	4.0	40	72/90	0.77	0.50	1.17
FRX055-90F	0.55	1.20	10.0	40	72/90	1.50	0.40	1.50
FRX065-90F	0.65	1.30	5.3	40	72/90	0.88	0.31	0.72
FRX075-90F	0.75	1.50	6.3	40	72/90	0.92	0.25	0.60
FRX090-90F	0.90	1.80	7.2	40	72/90	0.99	0.20	0.47
FRX110-90F	1.10	2.20	8.2	40	72/90	1.50	0.15	0.38
FRX135-90F	1.35	2.70	9.6	40	72/90	1.70	0.12	0.30
FRX160-90F	1.60	3.20	11.4	40	72/90	1.90	0.09	0.22
FRX185-90F	1.85	3.70	12.6	40	72/90	2.10	0.08	0.19
FRX250-90F	2.50	5.00	15.6	40	72/90	2.50	0.05	0.13
FRX300-90F	3.00	6.00	19.8	40	72/90	2.80	0.04	0.10
FRX375-90F	3.75	7.50	24.0	40	72/90	3.20	0.03	0.08


I_H=Hold current-maximum current at which the device will not trip at 23°C still air.
 I_T=Trip current-minimum current at which the device will always trip at 23°C still air.
 V_{MAX}=Maximum voltage device can withstand without damage at its rated current.
 I_{MAX}= Maximum fault current device can withstand without damage at rated voltage (V_{MAX}).
 Pd=Typical power dissipated from device when in tripped state in 23°C still air environment.
 R_{MIN}=Minimum device resistance at 23°C.
 R_{1MAX}=Maximum device resistance at 23°C, 1 hour after tripping .
 Physical specifications:
 Lead material: FRX010-90F~FRX090-90F Tin plated copper, 24 AWG.
 FRX110-90F~FRX375-90F Tin plated copper, 20 AWG.
 Soldering characteristics: MIL-STD-202, Method 208E.
 Insulating coating:Flame retardant epoxy, meets UL 94 V-0 requirement.
 * NOTE : TÜV is only applied for FRX040-90F~FRX375-90F.

NOTE : All Specifications subject to change without notice. 8

FRX90V Product Dimensions (Millimeter)




FRX 010-90F ~ FRX 090-90F
Lead Size : 24AWG
Φ 0.51 mm Diameter



FRX 110-90F ~ FRX 375-90F
Lead Size : 20AWG
Φ 0.81 mm Diameter


Part Number	A	B	C	D	E	F
	Maximum	Maximum	Typical	Minimum	Maximum	Typical
FRX010-90F	7.4	12.7	5.1	7.6	3.1	1.1
FRX015-90F	7.4	12.7	5.1	7.6	3.1	1.1
FRX017-90F	7.4	12.7	5.1	7.6	3.1	1.1
FRX020-90F	7.4	12.7	5.1	7.6	3.1	1.1
FRX025-90F	7.4	12.7	5.1	7.6	3.1	1.1
FRX030-90F	7.4	13.0	5.1	7.6	3.1	1.1
FRX035-90F	7.4	12.7	5.1	7.6	3.1	1.1
FRX040-90F	7.6	13.5	5.1	7.6	3.1	1.1
FRX050-90F	7.9	13.7	5.1	7.6	3.1	1.1
FRX055-90F	9.7	14.0	5.1	7.6	3.1	1.1
FRX065-90F	9.7	14.5	5.1	7.6	3.1	1.1
FRX075-90F	10.4	15.2	5.1	7.6	3.1	1.1
FRX090-90F	11.7	15.8	5.1	7.6	3.1	1.1
FRX110-90F	13.0	18.0	5.1	7.6	3.1	1.4
FRX135-90F	14.5	19.6	5.1	7.6	3.1	1.4
FRX160-90F	16.3	21.3	5.1	7.6	3.1	1.4
FRX185-90F	17.8	22.9	5.1	7.6	3.1	1.4
FRX250-90F	21.3	26.4	10.2	7.6	3.1	1.4
FRX300-90F	24.9	30.0	10.2	7.6	3.1	1.4
FRX375-90F	28.5	33.5	10.2	7.6	3.1	1.4

Thermal Derating Curve




Typical Time-To-Trip at 23°C


- A = FRX010-90F
- B = FRX015-90F
- C = FRX017-90F
- D = FRX020-90F
- E = FRX025-90F
- F = FRX030-90F
- G = FRX035-90F
- H = FRX040-90F
- I = FRX050-90F
- J = FRX055-90F
- K = FRX065-90F
- L = FRX070-90F
- M = FRX090-90F
- N = FRX110-90F
- O = FRX135-90F
- P = FRX160-90F
- Q = FRX185-90F
- R = FRX250-90F
- S = FRX300-90F
- T = FRX375-90F



Part Numbering System



Part Marking System



Standard Package

P/N	Pcs /Bag	Reel/Tape
FRX010-90F	500	3K
FRX015-90F	500	3K
FRX017-90F	500	3K
FRX020-90F	500	3K
FRX025-90F	500	3K
FRX030-90F	500	3K
FRX035-90F	500	3K
FRX040-90F	500	3K
FRX050-90F	500	3K
FRX055-90F	500	3K

P/N	Pcs /Bag	Reel/Tape
FRX065-90F	300	3K
FRX075-90F	300	3K
FRX090-90F	300	3K
FRX110-90F	200	1.5K
FRX135-90F	200	1.5K
FRX160-90F	200	1.5K
FRX185-90F	200	1.5K
FRX250-90F	100	-----
FRX300-90F	100	-----
FRX375-90F	100	-----

Warning:

- Operation beyond the specified maximum ratings or improper use may result in damage and possible electrical arcing and/or flame.
- PPTC device are intended for occasional overcurrent protection. Application for repeated overcurrent condition and/or prolonged trip are not anticipated.
- Avoid contact of PPTC device with chemical solvent. Prolonged contact will damage the device performance.

