

Item no.: 279-101
 Product description: 2-CONDUCTOR THROUGH TERMINAL BLOCK; LATERAL MARKING; CARRIER RAIL DIN 35; SIDE-ENTRY; CAGE CLAMP®CONNECTION; HORIZONTAL TYPE



Packing unit 100 pieces

Cross section from [mm ²]	0,08 mm ²
Cross section to [mm ²]	1,5 mm ²
Cross section from [AWG]	28 AWG
Cross section to [AWG]	16 AWG
Connection method	CAGE CLAMP®CONNECTION
Voltage CSA	600 V
Voltage UL	600 V
Current UL	10 A
Current CSA	15 A
Measured voltage EN	800 V
Measured shock voltage	8 kV
Pollution degree	3
Current intensity EN	18 A
Weight	3,25 g
Color	grey
Wiring type	Side-entry
No. of connection Points	2
No. of potentials	1
Height	30,5 mm
Height	1,2 in
Width	4 mm
Width	0,157 in
Depth	42,5 mm
Depth	1,67 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0,33 in

	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
279-101	BBJ	B/12/700/03	800	18	1,5
279-101	BV	07436/Co	800	18	1,5
279-101	CSA	154112-1327715	600	15	28-16
279-101	CSM	017956	800	18	1,5
279-101	DEMKO	76763	750		1,5
279-101	Dep.MaE	CS4864N	600	15	1,5
279-101	DNV	E-6999	800	18	1,5
279-101	GL	17295-00HH	800	18	1,5
279-101	KEMA	98.2759.02	800		1,5
279-101	KR	HMB05880-EL001	800	19,5	1,5
279-101	LR	91/29112(E1)	800	18	1,5

279-101	NEMKO	M52725	750		1,5
279-101	PRS	TE/1219/880590/98	800	18	1,5
279-101	RMR	99.00007.250	800	18	1,5
279-101	RosTesT	B09523	800	18	1,5
279-101	SABS	751/82640	750		1,5
279-101	SEMKO	9410109	750		1,5
279-101	UL	E45172	600	10	28-16

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected