



Kjack: 2.5 ZS C8113

RATING: DC30V 0.3A

WITHSTAND VOLTAGE: AC500V(50Hz)/min

CONTACT RESISTANCE: $\leq 30m\Omega$

INSULATION RESISTANCE: $\geq 100M\Omega$

WITHDRAW FORCE: 3-25N

LIFE TEST: 5,000 cycles

RoHS Compliant				SEMIC TRADE, s.r.o. Volutová 2521/18 158 00 Praha 5 Czech Republic	www.semic.cz semic@semic.cz tel.: +420 251 625 331, 332, 377 fax: +420 251 626 252, 393
APPD. 核准	Betty		TOLERANCE 容許公差 .0 \pm 0.30 .00 \pm 0.20 ANG. \pm 3°	PART NAME 品名 ϕ 2.5mm PHONE JACK SMT TYPE ALL PLASTIC WITH TWO LOCATING PEGS SILVER PLATING BLACK INSULATOR ROHS	
DWG. 製圖	Betty		SCALE 比例 參考 UNIT 單位 M M	PART NO. 料號 C8113-03PAVB00R	
DATE 制表日	2012/10/23		PAGE 張數 1 OF 1	REV. 版次 A	

6				
5				
4				
3				
2	TERMINAL	BRASS	3	Ag-Plating
1	HOUSING	PA66	1	BLACK
NO.	DESCRIPTION	MATERIAL	QTY.	PLATING