

PCB Layout







Krj12 Z6/6DSGF1BAR C65

Materials

Housing: Glass Filled Polyester UL94V-0,Black

Shielding: 0.25mm Thick Copper Alloy,Tin-plated

Contact: 0.35mm Thick Alloy, C5210 Selective Gold Plating

General tolerance: ±0.2mm General angle tolerance: ±2°

RoHS Compliant

SEMIC TRADE

SEMIC TRADE, s.r.o.
Volutová 2521/18
158 00 Praha 5
Czech Republic
www.semic.cz
semic@semic.cz
tel.: +420 251 625 331, 332, 377
fax: +420 251 626 252, 393

APPD. 核准 HELEN	SCALE 比例 參考	TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名: SIDE ENTRY P.C.B. JACK 6PXC DIP W/PANEL STOP(SHIELDED) BLACK INSULATOR ROHS
DWG. 製圖 ABBY	UNIT 單位 MM	SIZE. 紙張尺寸 A4	PART NO. 料號: C0065-6XPCXB00R
DATE 制表日 2011/10/11	PAGE 張數 1 OF 1	REV. 版次 A	





MATERIAL AND FINISH

Housing: Standard Material Glass Filled Polyester UL 94V-0
Standard Color Black.
Contact: 0.35mm Thickness Phosphor Bronze,
Shielded: 0.25mm Thickness Copper Alloy With Tin/Nickel Plated.
Gold Plating: Selective Gold Plating.

ELECTRICAL:

1. Current Rating : 1.5 AMP
2. Voltage Rating : 150 VAC
3. Contact Resistance : 20 Milliohms MAX
4. Insulation Resistance : 500 Milliohms MIN
5. Dielectric Withstanding Voltage : 1000 VAC, 1min





SUGGESTED PCB LAYOUT
(COMPONENT SIDE)

RoHS Compliant

SEMIC TRADE

SEMIC TRADE, s.r.o.
Volutová 2521/18
158 00 Praha 5
Czech Republic
www.semic.cz
semic@semic.cz
tel.: +420 251 625 331, 332, 377
fax: +420 251 626 252, 393

APPD. 核 准	BETTY
DWG. 製 圖	BETTY
DATE 制表日	2008/07/01
SCALE 比 例	參 考
UNIT 單 位	M M
PAGE 張 數	1 OF 1
容許公差 TOLERANCE	.000 ±0.13 ANG±3° .00 ±0.25 .0 ±0.38
SIZE. 紙張尺寸	A 4
REV. 版 次	A

PART NAME 品 名
SIDE ENTRY P.C.B. JACK 6P6C DIP W/PANEL STOP(SHIELDED)
FLAT PIN BLACK INSULATOR ROHS LOW-LEAD

PART NO. 料 號 C0065-66PCXB00R