

PCB Layout



Krj45 Z8/8DSGF2BNR C60





Materials

Housing: Glass Filled Polyester UL94V-0,Black

Shielding: 0.25mm Thick Copper Alloy,Tin-plated

Contact: 0.45mm Diameter Phosphor Bronze
Gold Plating Over Nickel

General tolerance: ±0.2mm General angle tolerance: ±2°

Electrical Characterisitics:

Insulation Resistance:500MΩ Min.
Contact Resistance:30mΩ Max.
Withstand Voltage:1000VAC 1minute.
Current Rating:1.5A

RoHS Compliant

SEMIC TRADE

SEMIC TRADE, s.r.o.
Volutová 2521/18
158 00 Praha 5
Czech Republic
www.semic.cz
semic@semic.cz
tel.: +420 251 625 331, 332, 377
fax: +420 251 626 252, 393

APPD. 核准 HELEN	SCALE 比例 參考	TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名: SIDE ENTRY PCB JACK STAMPED PIN 10P8C GANG TYPE 2 PORTS FULLY SHIELDED B TYPE WITH 3 TABS BLACK INSULATOR ROHS
DWG. 製圖 ABBY	UNIT 單位 MM	SIZE. 紙張尺寸 A4	
DATE 制表日 2015/10/26	PAGE 張數 1 OF 1	REV. 版次 C	PART NO. 料號 C0060-08BBXB02R