Product Info ...



Type: Product Name: Description: FB-25-02 5521 4p ear PCB JACK ELECTRICAL


CURRENT RATING:1.5AMPS
VOLTAGE RATING:125VAC

INSULATION RESISTANCE:100MEGOHMS MINI

WITHSTAND VOLTAGE:AC 1000V RMS 50Hz or

60Hz 1 MIN

CONTACT RESISTANCE:20MILLMHOS MINI







MECHANICAL

INSERTIONFORCE:2CONTACTS..350g 4CONTACTS..500g 6CONTACTS..750g 8CONTACTS..900g 10CONTACTS..1050g

RETENTION STRENGTH:7.7Kg BETWEEN JACK AND PLUG CRIMP TENSILE STRENGTH:2.27Kg DURABILITY: 750MATING CYCLES MIN

MATERIAL

HOUSING:1)ABS RESIN(UL94V-0) 2)GLASS FILLED PBT(UL94V-0) CONTACT WIRE:1)0.45mm DIA PHOSPHOR BRONZE GOLD

PLATING OVER NICKEL

2)0.35mm THICKNESS PHOSPHOR BRONZE

ALLOY SELECTIVE GOLD PLATING OVER NICKEL
SHIELDING: 0.25mm THICKNESS COPPER ALLOY WITH TIN PLATED
GOLD PLATING: 3INCH.6u INCH.15u INCH.30u INCH.50u INCH