


PIN NO.	DESCRIPTION
P1#	C1:VCC
P2#	C5:GND
P3#	C2:RST
P4#	C6:VPP
P5#	C3:CLK
P6#	C7:I/O
P7#	CD SW LOWER
P8#	CD SW UPPER

Specification


- * Electrical Characteristics :
 - Current Rating: 0.5A AC/DC Max.
 - Dielectric Withstanding Voltage: 250V AC/DC
 - Insulation Resistance: 500M ohms Min.
 - Contact Resistance: 100m ohms Max.
- * Mechanical Characteristics:
 - Mating Cycles: 5000 Insertions.
- * Environmental :
 - Operating Temperature: -40°C to +85°C.
- * Material:
 - 1.Housing:HI-Temp plastic UL 94V-0 Rated.
 - 2.Contact:Copper Alloy.
 - 3.Shell:Stainless Steel SUS 304,t=0.20mm.
- * Plating :
 - Terminal:
 - Contact area: Gold Flash Plated Over 40u"

Nickel.

- Solder area: 80u" Tin Plated Over 40u" Nickel.
- Under plate: 40u"Min. Nickel.
- Shell:
 - 30u"Min. Nickel Plated Over All,
 - Solder Area: Gold Flash.



SIM 示意图
芯片面朝下视图



RECOMMENDED PCB LAYOUT(TOP VIEW)
GENERAL TOLERANCES:±0.05
SOLDER AREA

<p>RoHS Compliant</p>		<p>SEMIC TRADE</p>		<p>SEMIC TRADE, s.r.o. Volutova 2521/18 158 00 Praha 5 Czech Republic</p>		<p>www.semic.cz semic@semic.cz tel.: +420 251 625 331, 332, 377 fax: +420 251 626 252, 393</p>	
<p>APPD. 核准</p>	<p>SCALE 比例</p>	<p>DIMENSION IN mm (inch)</p> <p>TOLERANCE UNLESS OTHERWISE SPECIFIED</p> <p>.XX±0.3 .X"±.01"</p> <p>.XX±0.2 .X"±</p> <p>.XXX±0.1 .XX"±</p>	<p>PART NAME 品名</p> <p>SIM CARD PUSH-PUSH TYPE</p> <p>SMT TYPE 6P WITH POST & WITH SWITCH BLACK COLOR TAPE & REEL PACKING ROHS</p>				
<p>DWG. 製圖</p> <p>Betty</p>	<p>UNIT 單位</p> <p>M M</p>	<p>SIZE. 紙張尺寸</p> <p>A 4</p>	<p>PART NO. 料號</p> <p>C0621-06YXBR02R</p>				
<p>DATE 制表日</p> <p>2020/05/29</p>	<p>PAGE 張數</p> <p>1 OF 1</p>	<p>REV. 版次</p> <p>A</p>					

Ksim:C0621-06YHB