


PCB LAYOUT  
(BOTTOM VIEW)



Kusb 8317-08DR

Specification:

Contact Resistance: 30m Ohm Max.

Insulation Resistance: 1000M Ohm Min. At 500VDC.

Rated Voltage And Current: 1.5A At 250VAC Minimum.

Dielectric Withstanding Voltage: 750V AC (rms) for 1 Minute (Rev. 1.1).

Durability (Life Test): 1500 Cycles.

Insertion Force: 35 Newton Maximum.

Extraction Force: 10 Newton Minimum.

| NO. | NAME        | MATERIAL             | FINISH          | Q'TY | REMARK   |
|-----|-------------|----------------------|-----------------|------|--|
| 1   | HOUSING     | PBT G.F.             | WHITE           | 1    |  |
| 2   | PIN TERM.   | PHOS. BRONZE, T:0.25 | GOLD-TIN PLATED | 8    | Gold(1~3u") NI(4~60u") TIN(20u")<br>(100% pure Tin or lead free plating) |
| 3   | SHELL       | BRASS, T:0.3         | NICKEL PLATED   | 1    | NI:80~120u"  |
| 4   | SPRING CLIP | BRASS, T:0.3         | NICKEL PLATED   | 1    | NI:80~120u"  |
| 5   | REAR SHELL  | SPCC, T:0.3          | NICKEL PLATED   | 1    | NI:80~120u"  |

**RoHS**  
Compliant

**SEMIC**  
TRADE

SEMIC TRADE, s.r.o.  
Volutová 2521/18  
158 00 Praha 5  
Czech Republic  
www.semic.cz  
semic@semic.cz  
tel.: +420 251 625 331, 332, 377  
fax: +420 251 626 252, 393

APPD.  
核准

DWG.  
製圖

DATE  
制表日

2012/08/03



SCALE  
比例

UNIT  
單位

PAGE  
張數

1 / 1

TOLERANCE  
容許公差  
X, ±0.38  
Y, ±0.25  
XX, ±0.13  
XXX, ±0.05

SIZE  
紙張尺寸

REV.  
版次

A

PART NAME 品名

USB A TYPE DIP TYPE 8P FEMALE 90° HORIZONTAL TIN SHELL  
SELECTIVE GOLD PLATING(1.1VER) WHITE COLOR  
W/O EMI TABS ROHS

PART NO.

料號 C8317-08CFHSW1R