



LTR	Part Name	Material	Description	QTY
1	Housing	LCP UL94V-0	260°C for 10 Seconds . Initial : 1000M Ohms Min. After Test : 500M Ohms Min.	1
2	Contact	Bronze C5191	Current Rating : 0.75A Initial : 20m Ohms Max. After Test : 40m Ohms Max.	XX

Temperature Rating : -40°C ~ +125°C .
Dielectric Withstanding Voltage : 500V AC/Min .

APPD. 核准	SCALE 比例 参考	General Tolerance		PART NAME 品名
		X ± 0.5	Y ± 0.3	
DWG. 製圖	UNIT 單位	.XX ± 0.2		DUAL ROW SMT TYPE 2XXXP H=3.1mm WITHOUT LOCATING PEG ROHS
		.XXX ± 0.1		
DATE 制表日	PAGE 張數	角度 ± 5°		PART NO. 料號
		SIZE. 紙張尺寸		
2018/02/27	1 OF 1	REV. 版次	C	C5910-XXBDXHNT

RoHS Compliant

SEMIC TRADE

SEMIC TRADE, s.r.o. www.semic.cz
 Volutová 2521/18 semic@semic.cz
 158 00 Praha 5 tel.: +420 251 625 331, 332, 377
 Czech Republic fax: +420 251 626 252, 393