



VISIBLE LIGHT PRODUCTS

(Light Emitting Diode)

REV:C
DATE:2006/5/25

☰ DEVICE NO:H16/1I-14 (Hi-Eff Red)

☰ LENS COLOR:

✓	colored diffusion	colored transparent	white diffusion	water clear
---	-------------------	---------------------	-----------------	-------------

☰ PACKAGE DIMENSIONS:

NOTE:

- 1.All dimensions are in millimeter.
- 2.Lead spacing is measured where the lead emerge from the package.
- 3.prodruded resin under flange is 1.5mm max.
- 4.specifications are subject to change without notice.
- 5.Tolerance is 0.3mm unless otherwise noted.

☰ ABSOLUTE MAXIMUM RATINGS:

Material:GaAsP/GaP

TA=25°C

PARAMETER	SYMBOL	MAX. RATING	UNIT
Power Dissipation	Pd	90	mW
Continuous Forward Current	IF	30	mA
Peak Forward Current *1	IFM	50	mA
Reverse Voltage	VR	5	V
LED Junction Temperature	Tj	100	°C
Operating Temperature	Topr	-25 ~ +85	°C
Storage Temperature	Tstg	-40 ~ +100	°C
Dip Soldering Temperature (3mm from case Bottom 260 °C for 5 seconds)			

☰ ELECTRIC-OPTICAL CHARACTERISTICS:

TA=25°C

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
View Angle of Half Power	2θ1/2	IF=20mA		60		Degree
Forward Voltage	VF	IF=20mA		2.05	2.80	V
Reverse Current	IR	VR=5V			10	uA
Luminous Intensity *2	IV	IF=20mA	20	35		mcd
Peak Emission Wavelength	λp	IF=20mA		625		nm
Dominate Wave Length *3	λd(HUE)	IF=20mA		618		nm
Spectrum Width of Half Valve	Δλ	IF=20mA		45		nm
Terminal Capacitance	Ct	V=0V F=1MHz		6		pF
Response Frequency	Fc	-----		4		MHz

*1.Duty Ratio=1/10,Pulse Width=0.1ms.

*2.Tolerance:30% HUEY-JANN measuring equipment :1.EXELTRON 2001. 2.S370 made by U.D.T.

*3.The dominate wavelength, λd, is derived from the CIE Chromaticity Diagram and represents the color of the device.



SEMIC TRADE, s.r.o.
Volutová 2521/18
158 00 Praha 5
Czech Republic

www.semic.cz
semic@semic.cz

tel.: +420 251 625 331, 332, 377
fax: +420 251 626 252, 393