


# SK250MB120CR03TE2V1



**SEMITOP®E2**

## Half-Bridge (Full SiC)

### Engineering Sample SK250MB120CR03TE2V1

#### Target Data

#### Features\*

- Optimized design for superior thermal performance
- Extremely low inductance design
- Press-Fit contact technology
- 1200V Planar Gen3 SiC MOS
- Simple to drive with +15V gate voltage
- Integrated NTC temperature sensor
- UL recognized file no. E 63 532

#### Typical Applications

- Switched Mode Power Supplies
- Energy Storage Systems
- Electric Vehicle charging
- UPS
- Solar
- Motor Drives

#### Remarks

- Recommended  $T_{j,op} = -40 \dots +150 \text{ °C}$
- Recommended turn-off / turn-on gate voltage  $V_{GS} = -4 \dots 0 / +15 \text{ V}$

#### Footnotes


<sup>1)</sup> SEMIKRON Exclusive High Performance Thermal Paste (HPTP), available as pre-applied

#### Absolute Maximum Ratings

Symbol	Conditions		Values	Unit
MOSFET 1				
V <sub>DSS</sub>			1200	V
I <sub>D</sub>	T <sub>j</sub> = 175 °C	T <sub>s</sub> = 25 °C	266	A
		T <sub>s</sub> = 70 °C	223	A
I <sub>DM</sub>	Pulse width t <sub>p</sub> limited by T <sub>jmax</sub>		720	A
I <sub>DM,repetitive</sub>			400	A
V <sub>GS</sub>	Max. transient gate - source voltage		-8 ... 19	V
T <sub>j</sub>			-55 ... 175	°C
Integrated body diode				
I <sub>FM</sub>	Pulse width t <sub>p</sub> limited by T <sub>jmax</sub>		720	A
I <sub>FM,repetitive</sub>			400	A


#### Absolute Maximum Ratings

Symbol	Conditions	Values	Unit
<b>Module</b>			
$I_{t(RMS)}$	$\Delta T_{terminal}$ at PCB joint = 30 K, per pin	30	A
$T_{stg}$		-40 ... 125	°C
$V_{isol}$	AC, sinusoidal, $t = 1 \text{ min}$	2500	V



**MB-T**

# SK250MB120CR03TE2V1



SEMITOP®E2

## Half-Bridge (Full SiC)

### Engineering Sample SK250MB120CR03TE2V1

#### Target Data

#### Features\*

- Optimized design for superior thermal performance
- Extremely low inductance design
- Press-Fit contact technology
- 1200V Planar Gen3 SiC MOS
- Simple to drive with +15V gate voltage
- Integrated NTC temperature sensor
- UL recognized file no. E 63 532

#### Typical Applications

- Switched Mode Power Supplies
- Energy Storage Systems
- Electric Vehicle charging
- UPS
- Solar
- Motor Drives

#### Remarks

- Recommended  $T_{j,op} = -40 \dots +150 \text{ }^{\circ}\text{C}$
- Recommended turn-off / turn-on gate voltage  $V_{GS} = -4 \dots 0/+15\text{V}$


#### Footnotes

<sup>1)</sup> SEMIKRON Exclusive High Performance Thermal Paste (HPTP), available as pre-applied

Characteristics					
Symbol	Conditions	min.	typ.	max.	Unit
<b>MOSFET 1</b>					
$V_{(BR)DSS}$	$V_{GS} = 0 \text{ V}, I_D = 0.1 \text{ mA}, T_j = 25 \text{ }^{\circ}\text{C}$	1200			V
$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 69 \text{ mA}, T_j = 25 \text{ }^{\circ}\text{C}$	1.8	2.5	3.6	V
$I_{DSS}$	$V_{GS} = 0 \text{ V}, V_{DS} = 1200 \text{ V}, T_j = 25 \text{ }^{\circ}\text{C}$			1	mA
$I_{GSS}$	$V_{DS} = 0 \text{ V}, V_{GS} = 15 \text{ V}, T_j = 25 \text{ }^{\circ}\text{C}$			600	nA
$R_{DS(on)}$	$V_{GS} = 15 \text{ V}$				
	$I_D = 248 \text{ A}$				
	$T_j = 25 \text{ }^{\circ}\text{C}$		5.3	7.2	mΩ
	chipllevel		8.3		mΩ
$C_{iss}$	$V_{GS} = 0 \text{ V}, V_{DS} = 1000 \text{ V}, f = 0.1 \text{ MHz}$		20400		pF
$C_{oss}$	$V_{GS} = 0 \text{ V}, V_{DS} = 1000 \text{ V}, f = 0.1 \text{ MHz}$		780		pF
$C_{rss}$	$V_{GS} = 0 \text{ V}, V_{DS} = 1000 \text{ V}, f = 0.1 \text{ MHz}$		60		pF
$R_{Gint}$	$T_j = 25 \text{ }^{\circ}\text{C}$		2.3		Ω
$Q_G$	$V_{DD} = 800 \text{ V}, V_{GS} = -4 \text{ V} \dots 15 \text{ V}, I_D = 248 \text{ A}$		708		nC
$t_{d(on)}$	$V_{DD} = 600 \text{ V}$		51		ns
$t_{d(off)}$	$V_{GS} = 15/-4 \text{ V}$		129		ns
$t_r$	$I_D = 240 \text{ A}$		16		ns
$t_f$	$R_{G on/off} = 0.5 \text{ } \Omega$		16		ns
$E_{on}$	$di/dt_{off} = 18 \text{ kA}/\mu\text{s}$		2.03		mJ
$E_{off}$	$di/dt_{on} = 22 \text{ kA}/\mu\text{s}$		2.75		mJ
$R_{th(j-s)}$	per MOSFET, $\lambda_{paste} = 2.5 \text{ W}/(\text{mK})$ <sup>1)</sup>		0.21		K/W
<b>Integrated body diode</b>					
$V_F = V_{SD}$	$-I_D = 124 \text{ A}$		4.6		V
	$V_{GS} = -4 \text{ V}$				
	chipllevel		4.3		V
$V_{F0} = V_{SD0}$			3.8		V
	chipllevel		3.6		V
$r_F = r_{SD}$			6.4		mΩ
	chipllevel		5.6		mΩ
$t_{rr}$	$V_{DD} = 600 \text{ V}$		36		ns
$Q_{rr}$	$-I_D = 240 \text{ A}$		4.5		μC
$I_{rr}$	$V_{GS} = -4 \text{ V}$		251		A
$E_{rr}$	$R_{Gon} = 0.5 \text{ } \Omega$		1.33		mJ
	$di/dt_{off} = 20 \text{ kA}/\mu\text{s}$				

Characteristics					
Symbol	Conditions	min.	typ.	max.	Unit
<b>Module</b>					
$L_{CE}$			6		nH
$M_s$	to heatsink	1.6		2.3	Nm
$w$	weight		35		g

Characteristics					
Symbol	Conditions	min.	typ.	max.	Unit
<b>Temperature Sensor</b>					
$R_{100}$	$T_r = 100 \text{ }^{\circ}\text{C}$		$493 \pm 5\%$		Ω
$B_{100/125}$	$R(T) = R_{100} \exp[B_{100/125}(1/T - 1/T_{100})]$ ; $T[K]$		$3550 \pm 2\%$		K



MB-T




Fig. 1: Typ. MOSFET forward output characteristic, incl.  $R_{DD'}+SS'$




Fig. 2: Typ. MOSFET reverse output characteristics, incl.  $R_{DD'}+SS'$




Fig. 3: Rated current vs. temperature  $I_D = f(T_S)$




Fig. 4: Typ. turn-on/-off energy  $E = f(I_D)$




Fig. 5: Typ. turn-on /-off energy  $E = f(R_G)$




Fig. 6: Typ. MOSFET transfer characteristic




Fig. 7: Typ. MOSFET gate charge characteristic




Fig. 8: Typ. switching times  $t = f(I_D)$




Fig. 9: Typical switching times  $t = f(R_G)$




Fig. 10: Typ. diode peak reverse recovery current  $I_{RR} = f(di_F/dt)$




Fig. 11: Typ. diode peak reverse recovery charge  $Q_{RR} = f(di_F/dt)$









Fig. 12: MOSFET Reverse Bias Safe Operating Area (RBSOA)




# SK250MB120CR03TE2V1



- Pin-Grid 3.2 mm
- Tolerance of PCB hole pattern  $\pm 0.1$
- Diameters of drill  $\varnothing 1.15\text{mm}$
- Copper thickness in hole 25 - 50  $\mu\text{m}$
- Hole specification for contacts:  
refer to SEMITOP E1/E2 Mounting Instruction

SEMITOP®E2



MB-T

This is an electrostatic discharge sensitive device (ESDS) due to international standard IEC 61340.

## **\*IMPORTANT INFORMATION AND WARNINGS**

The specifications of SEMIKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMIKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMIKRON makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMIKRON reserves the right to make changes.

In accordance with the quality guidelines of SEMIKRON, we would like to point out that the products are engineering samples. These engineering samples are not yet produced under quality conditions approaching those of series production, and are at the present time not included in the SEMIKRON quality monitoring and control process. Neither the product nor the production process has to date gone completely through the SEMIKRON internal authorization procedure. SEMIKRON may make any amendments without any prior notification. SEMIKRON cannot and shall not promise or commit itself to release and/or make available a final version or series product after the development phase. SEMIKRON cannot and will not assume any responsibility with regard to freedom from defects, functionality, and adaptation to and interaction with possible applications of the user or with regard to any other potential risks resulting from the use of engineering samples. Therefore SEMIKRON explicitly excludes any warranty and liability; as far as legally possible. The customer shall fully indemnify and hold harmless SEMIKRON from any and all risks, damages, losses, expenses and costs directly or indirectly resulting out of or in connection with the commissioning, operation, system integration, sale, dissemination or any other kind of use of engineering samples by the customer and/or any third party, which has come into possession of engineering samples through or because of the customer. All know-how and all registerable and non-registerable copyrights and industrial property rights arising from or in connection with these engineering samples remain the exclusive property of SEMIKRON.