

SiC MOSFET Module


SK25MH120SCTp

Features*

- Low inductance design
- One screw mounting module
- Fully compatible with other SEMIPRESS® Press-Fit types
- Improved thermal performance by aluminum oxide substrate
- 1200V Planar Gen2 SiC MOS
- Integrated NTC temperature sensor
- UL recognized, file no. E63532

Typical Applications

- Switched Mode Power Supplies
- Energy Storage Systems
- Electric Vehicle charging



Absolute Maximum Ratings				
Symbol	Conditions		Values	Unit
MOSFET 1				
V _{DSS}			1200	V
I _D	T _j = 175 °C	T _s = 25 °C	25	A
		T _s = 70 °C	21	A
I _{DM}	PW≤10μs, duty cycle≤1%		140	A
I _{DM,repetitive}			40	A
V _{GS}			-6 ... 22	V
T _j			-40 ... 175	°C
Integrated body diode				
I _{FM}	PW ≤ 10μs, Duty cycle ≤ 1%		140	A
I _{FM,repetitive}			40	A

Absolute Maximum Ratings			
Symbol	Conditions	Values	Unit
Module			
I _{t(RMS)}	ΔT _{terminal} at PCB joint = 30 K, per pin	35	A
T _{stg}		-40 ... 125	°C
V _{isol}	AC, sinusoidal, t = 1 min	2500	V

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
MOSFET 1						
V _{(BR)DSS}	V _{GS} = 0 V, I _D = 1 mA, T _j = 25 °C		1200			V
V _{GS(th)}	V _{DS} = V _{GS} , I _D = 4.4 mA, T _j = 25 °C		1.6	2.8	4	V
I _{DSS}	V _{GS} = 0 V, V _{DS} = 1200 V, T _j = 25 °C				1	mA
I _{GSS}	V _{DS} = 0 V, V _{GS} = 22 V, T _j = 25 °C				100	nA
R _{DS(on)}	V _{GS} = 18 V	T _j = 25 °C		80	111	mΩ
	I _D = 10 A chiplevel	T _j = 150 °C		124		mΩ
C _{iss}	V _{GS} = 0 V, V _{DS} = 800 V, f = 1 MHz			2070		pF
C _{oss}	V _{GS} = 0 V, V _{DS} = 800 V, f = 1 MHz			80		pF
C _{rss}	V _{GS} = 0 V, V _{DS} = 800 V, f = 1 MHz			20		pF
R _{Gint}	T _j = 25 °C			9.0		Ω
Q _G	V _{DD} =600V, V _{GS} =-5V...+18V, I _D = 10 A			121		nC
t _{d(on)}	V _{DD} = 600 V	T _j = 150 °C		18		ns
t _{d(off)}	V _{GS} = 20/-5 V	T _j = 150 °C		60		ns
t _r	I _D = 25 A	T _j = 150 °C		45		ns
t _f	R _{G on/off} = 0.5 Ω	T _j = 150 °C		12		ns
E _{on}	di/dt _{off} = 1.2 kA/μs	T _j = 150 °C		0.5		mJ
E _{off}	di/dt _{on} = 1.6 kA/μs	T _j = 150 °C		0.16		mJ
	dv/dt = 36 kV/μs	T _j = 150 °C				
R _{th(j-s)}	per MOSFET, λ _{paste} =0.8 W/(mK)			1.52		K/W
Integrated body diode						
V _F = V _{SD}	-I _D = 10 A	T _j = 25 °C		5.00		V
	V _{GS} = 0 V chiplevel	T _j = 150 °C		4.70		V
V _{F0} = V _{SD0}		T _j = 25 °C		2.50		V
	chiplevel	T _j = 150 °C		1.90		V
r _F = r _{SD}		T _j = 25 °C		250		mΩ
	chiplevel	T _j = 150 °C		280		mΩ
t _{rr}	V _{DD} = 600 V	T _j = 150 °C		70		ns
Q _{rr}	-I _D = 25 A	T _j = 150 °C		0.9		μC
I _{rr}	di/dt _{off} = 1.6 kA/μs	T _j = 150 °C		26		A
E _{rr}	V _{GS} = -5 V	T _j = 150 °C		0.24		mJ

SK25MH120SCTp



SEMITOP® 2 Press-Fit

SiC MOSFET Module

SK25MH120SCTp

Features*


- Low inductance design
- One screw mounting module
- Fully compatible with other SEMITOP® Press-Fit types
- Improved thermal performance by aluminum oxide substrate
- 1200V Planar Gen2 SiC MOS
- Integrated NTC temperature sensor
- UL recognized, file no. E63532

Typical Applications

- Switched Mode Power Supplies
- Energy Storage Systems
- Electric Vehicle charging

Characteristics					
Symbol	Conditions	min.	typ.	max.	Unit
Module					
L_{CE}			18		nH
M_s	to heatsink	1.8		2	Nm
w	weight		19		g

Characteristics					
Symbol	Conditions	min.	typ.	max.	Unit
Temperature Sensor					
R_{100}	$T_r = 100\text{ °C}$		$493 \pm 5\%$		Ω
$B_{100/125}$	$R(T) = R_{100} \exp[B_{100/125}(1/T - 1/T_{100})]$; $T[K]$		$3550 \pm 2\%$		K



MH-T




Fig. 1: Typ. MOSFET forward output characteristic, incl. $R_{DS(on)}$ and SS




Fig. 2: Typ. reverse output characteristic, incl. $R_{DS(on)}$ and SS




Fig. 3: Rated current vs. temperature $I_D = f(T_S)$




Fig. 4: Typ. turn-on/-off energy $E = f(I_D)$




Fig. 5: Typ. turn-on /-off energy $E = f(R_G)$




Fig. 6: Typ. MOSFET transfer characteristic




Fig. 7: Typ. MOSFET gate charge characteristic




Fig. 8: Typ. switching times vs. I_D




Fig. 9: Typ. switching times vs. gate resistor R_G at I_{D1}




Fig. 10: Typ. switching times vs. gate resistor R_G at I_{D2}




Fig. 11: Typ. transient thermal impedances




Fig. 12: SiC MOSFET Reverse Bias Safe Operating Area (RBSOA)




Fig. 13: Typ. peak reverse recovery current





Fig. 14: Typ. reverse recovery charge

Dimensions: mm

Tolerance system: ISO 2768-m



Suggested drilled hole diameter for terminal pins in the circuit board:


- minimum: 1.575 mm
- typical: 1.6 mm
- maximum: 1.625 mm

Suggested hole diameter for the mounting post in the circuit board:

- 2 mm

These documents are SEMIKRON properties. SEMIKRON reserves all copyrights. All copying and transmitting of this information requires written permission. For the case of industrial property rights, SEMIKRON reserves all rights.

SEMITOP 2 Press-Fit



This is an electrostatic discharge sensitive device (ESDS) due to international standard IEC 61340.

***IMPORTANT INFORMATION AND WARNINGS**

The specifications of SEMIKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMIKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMIKRON makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMIKRON reserves the right to make changes.